

**Unique identifier of the product-type:**

DRY-PRESSED CERAMIC TILES WITH WATER ABSORPTION  $E_b \leq 0.5\%$ ; Group BIa; GLAZED (GL)

**Intended use or uses:**

CERAMIC TILES FOR TILING OF FLOORS AND WALLS, INDOOR AND/OR OUTDOOR, INCLUDING STAIRS, IN BUILDINGS AND INDUSTRIAL FACILITIES

**Manufacturer:**

Ceramika Końskie Sp. z o.o.; ul. Ceramiczna 5; 26-200 Końskie

**System or systems of assessment and verification of constancy of performance of the construction product:**

ASSESSMENT SYSTEM: 4

**Harmonised standard:**

EN 14411:2012

**Declared performance**


ESSENTIAL CHARACTERISTICS	PERFORMANCE
Reaction-to-fire performance	A1 <sub>fl</sub> / A1
<b>Release of dangerous substances:</b>	
- Lead	NPD
- Cadmium	NPD
- other	NPD
<b>Breaking strength for:</b>	
- thickness $\geq 7,5$ mm	$\geq 1300$ N
- thickness $< 7,5$ mm	$\geq 700$ N
<b>Bond strength / adhesion for:</b>	
- cementitious adhesives	NPD
- dispersion adhesives	NPD
- reactive resin adhesives	NPD
- mortar	NPD
<b>Slipperiness</b>	NPD
<b>Thermal shock resistance</b>	Pass
<b>Durability, for:</b>	
- internal uses:	Pass
- external uses: freeze thaw resistance	Pass
Tactility	NPD

The performance of the product referred to above is consistent with the set of declared performance/s.

This declaration of performance is issued in accordance with the Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer specified above.

Signed for and on behalf of the manufacturer by:

**Magdalena Bąk**



**MAGDALENA BĄK**  
Kierownik Działu Kontroli Jakości

in Końskie, 01/02/2022