

DECLARATION OF PERFORMANCE

No CK 04/2022/1

Unique identifier of the product-type:

DRY-PRESSED CERAMIC TILES WITH WATER ABSORPTION $E_b \leq 0.5\%$; Group Bla; UNGLAZED (UGL)

Intended use or uses:

CERAMIC TILES FOR TILING OF FLOORS AND WALLS, INDOOR AND/OR OUTDOOR, INCLUDING STAIRS, IN BUILDINGS AND INDUSTRIAL FACILITIES

Manufacturer:

Ceramika Końskie Sp. z o.o.; ul. Ceramiczna 5; 26-200 Końskie

System or systems of assessment and verification of constancy of performance of the construction product:

ASSESSMENT SYSTEM: 4

Harmonised standard:

EN 14411:2012

Declared performance

ESSENTIAL CHARACTERISTICS	PERFORMANCE
Reaction-to-fire performance	A1 _{fl} / A1
Release of dangerous substances:	
- Lead	NPD
- Cadmium	NPD
- other	NPD
Breaking strenght for:	
- thickness $\geq 7,5$ mm	≥ 1300 N
- thickness $< 7,5$ mm	≥ 700 N
Bond strength / adhesion for:	
- cementitious adhesives	NPD
- dispersion adhesives	NPD
- reactive resin adhesives	NPD
- mortar	NPD
Slipperiness	NPD
Thermal shock resistance	Pass
Durability, for:	
- internal uses:	Pass
- external uses: freeze thaw resistance	Pass
Tactility	NPD


The performance of the product referred to above is consistent with the set of declared performance/s.

This declaration of performance is issued in accordance with the Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer specified above.

Signed for and on behalf of the manufacturer by:

Magdalena Bąk

in Końskie, 01/12/2022


MAGDALENA BĄK
Kierownik Działu Kontroli Jakości