

Unique identifier of the product-type:

DRY-PRESSED CERAMIC TILES WITH WATER ABSORPTION $E_b \leq 0.5\%$; Group BIa; GLAZED (GL)

Intended use or uses:

CERAMIC TILES FOR TILING OF FLOORS AND WALLS, INDOOR AND/OR OUTDOOR, INCLUDING STAIRS, IN BUILDINGS AND INDUSTRIAL FACILITIES

Manufacturer:

Ceramika Końskie Sp. z o.o.; ul. Ceramiczna 5; 26-200 Końskie

System or systems of assessment and verification of constancy of performance of the construction product:

ASSESSMENT SYSTEM: 4

Harmonised standard:

BS EN 14411:2012

Declared performance

ESSENTIAL CHARACTERISTICS	PERFORMANCE
Reaction-to-fire performance	A1 _{fl} / A1
Release of dangerous substances:	
- Lead	NPD
- Cadmium	NPD
- other	NPD
Breaking strength for:	
- thickness $\geq 7,5$ mm	≥ 1300 N
- thickness $< 7,5$ mm	≥ 700 N
Bond strength / adhesion for:	
- cementitious adhesives	NPD
- dispersion adhesives	NPD
- reactive resin adhesives	NPD
- mortar	NPD
Slipperiness	NPD
Thermal shock resistance	Pass
Durability, for:	
- internal uses:	Pass
- external uses: freeze thaw resistance	Pass
Tactility	NPD

The performance of the product(s) identified above is/are in conformity with the declared performance in the table above. The declaration of conformity is issued under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

Magdalena Bąk

in Końskie, 01/02/2022


MAGDALENA BĄK
 Kierownik Działu Kontroli Jakości